

Vehicle antenna 2.6 m with GPS antenna

PN (RN): **2036.100.45**

The antenna is designed for fixed installation on all types of wheeled and tracked vehicles. It has omnidirectional radiation pattern with vertical polarization. The antenna has a built-in GPS active receiving antenna. The antenna is primarily intended for RF2350 EPM mobile transceiver which has built-in GPS receiver. The antenna can be used with all RF13 mobile transceiver sets and RF2050 transceivers in (30–108) MHz band, i.e. the VHF I band. The antenna consists of a base and a two-element radiator.

Technical parameters

Frequency range	30 MHz to 88 MHz
VSWR	max. 3.5
Nominal impedance	50 Ω
Power rating	100 W CW
Gain	-4 dBi to +1 dBi
Antenna height	2.6 m
Maximum weight	2.7 kg
Connector	
VHF	BNC
GPS	SMA (female)
Length of disassembled radiator	1.27 m
Antenna base height	272 mm
Operating temperature	-55 °C to +55 °C
Surface finish	polyurethane lacquer
Color	olive
GPS ANTENNA SPECIFICATIONS	
Frequency range	L1, 1575.42 \pm 10 MHz
Preamplifier gain	26.5 dB
Noise figure	2.5 dB
Supply voltage	5 \pm 0.5 V

Supply current

< 40 mA

MESIT asd, s.r.o.

Sokolovská 573, Mařatice
686 01 Uherské Hradiště
Česká republika

asd@mesit.cz

T +420 572 522 200

F

www.mesitasd.cz