

# NJ13.1 - Small mains charger

Type designation: **NJ13.1**

PN (RN): **7025.100.11**

The small mains charger is used to charge a single RF13.13 (LiIon) battery pack.

## Technical parameters

|  |                        |
|--|------------------------|
| <b>Supply voltage</b>                      | mains 100 V to 240 V   |
| <b>Current consumption from mains</b>      |                        |
| • at supply voltage 100 V                  | max. 400 mA            |
| • at supply voltage 240 V                  | max. 200 mA            |
| <b>Charging current</b>                    | max. 2500 mA           |
| <b>Termination of charging</b>             |                        |
| • when the charging current reaches        | 0 mA to 50 mA          |
| • after time expiration                    | max. 22 hours          |
| <b>Operating temperatures for charging</b> | 0 °C to +35 °C         |
| <b>Dimensions [w x h x d]</b>              | 85 mm x 65 mm x 155 mm |
| <b>Weight (including power cable)</b>      | 0.7 kg                 |

## Documentation

|                                      |             |
|--------------------------------------|-------------|
| <b>NJ13.1 operating instructions</b> | 7025.010.12 |
|--------------------------------------|-------------|

## Set

| Type designation | PN (RN) | Name |
|------------------|---------|------|
|------------------|---------|------|

NJ13.1

7025.000.11

Small mains charger  
set

## Battery packs

**Type  
designation**

**PN (RN)**

**Name**

RF13.13

7000.100.22

Rechargeable battery  
pack