

# Headset

PN (RN): **2328.100.11, 2328.100.12**

Light-weight headband headset consists of a central housing unit supporting a microphone and earphone, are mounted on flexible boom arms which can be rotated and instantly configured to accommodate both left side or right side users. The headset can be connected to RF23 or RF2350 transceivers with U-229/U type connector.

**Headset 2328.100.11 includes the extra PTT key with velcro to fix on hand or weapon.**

## Operation features

- dynamic noise-canceling microphone,
- IP67 waterproof,
- MIL-STD military standards,
- big PTT,
- headband type.

## Technical parameters

### SPEAKER SPECIFICATION

<b>Type</b>	magnetodynamic
<b>Impedance</b>	300 $\Omega$ $\pm$ 15 %
<b>Frequency range</b>	200 Hz to 4000 Hz
<b>Sensitivity</b>	85 $\pm$ 3 dB/mW at 1 kHz
<b>Rated input power</b>	20 mW
<b>Maximum input power</b>	100 mW

### MICROPHONE SPECIFICATION

<b>Type</b>	magnetodynamic
<b>Impedance</b>	max. 150 $\Omega$ at 1 kHz
<b>Frequency range</b>	200 Hz to 4000 Hz
<b>Operating temperature</b>	-55 $^{\circ}$ C to +70 $^{\circ}$ C
<b>Humidity</b>	96 %
<b>Atmospheric pressure</b>	86 kPa–106 kPa