

# MA1302 - Vehicle support

Type designation: **MA1302**

PN (RN): **7018.100.21**

MA1302 vehicle support supplies #RF20# transceivers with power and charges battery packs for this transceiver in vehicles with 12 V or 27 V board mains (compatible with MIL-STD-1275B). When removed with the battery pack from the holder, the transceiver becomes portable and capable of normal operation.

## Technické parametry

<b>Napájecí napětí z palubní sítě vozidla</b>	12 V nebo 27 V
<b>Rozsah napájecího napětí</b>	10 V až 33 V
<b>Odběr proudu z palubní sítě vozidla</b>	max. 4 A
<b>Odběr proudu v pohotovostním režimu</b>	max. 3 mA
<b>Výstupní napětí</b>	max. 9 V
<b>Napájecí proud do radiostanice</b>	min. 3,5 A
<b>Nabíjecí proud BP1301</b>	150 mA
<b>Nabíjecí proud LP1302, LP20</b>	max. 1,8 A
<b>Nabíjecí napětí pro BP1301</b>	max. 9 V
<b>Nabíjecí napětí pro LP1302</b>	max. 8,4 V
<b>Rozsah teploty zdrojové skříně pro nabíjení</b>	0 °C až 43 °C
<b>Rozsah pracovních teplot</b>	-40 °C až +70 °C
<b>Rozměry [š x v x h]</b>	215 mm x 200 mm x 60 mm
<b>Hmotnost</b>	max. 1 kg

## Průvodní dokumentace

<b>Návod k obsluze MA1302</b>	7018.010.21
<b>Záznamník</b>	6000002011

## Set

Type designation	PN (RN)	Name
MA1302	7018.000.26	Vehicle support set

## Battery packs

Type designation	PN (RN)	Name
LP1302	7029.100.02	Battery pack
LP20	7029.100.11, 7029.100.13	Battery pack