

RC20 - Remote control unit

Type designation: **RC20**

PN (RN): **2312.100.01**

The remote control unit is intended for remote control of RF2050 mobile transceivers. It is recommended to be used wherever the transceiver size or location make it difficult for the operators to access its controls and indicator elements. The RC20 has the same controls as the transceiver and therefore the control method is identical. Operating information is displayed on an active OLED display, which ensures good readability in low light conditions. There are two ten-pin connectors at the top of the remote control panel - one is used to connect the RC20 panel with the REMOTE transceiver connector, the other connector is identical with the AF transceiver connector - it allows you to connect the handset. Vehicle installation using 4 M5 screws, spacing of holes (102 x 107) mm.

Technické parametry

Rozsah napájecího napětí	7 V až 15 V
Maximální příkon	2 W
Typ komunikačního protokolu	PRC20
Typ komunikační linky	RS232 nebo RS485, nastavitelný radiostanicí
Parametry asynchronní komunikační linky	asynchronní, 57600 Bd
Maximální délka propojovacího kabelu	10 m (RS232) nebo 100 m (RS485)
Rozměry	120 mm x 147 mm x 44 mm [š x v x h]
Hmotnost	0,8 kg
Rozsah pracovních teplot	-30 °C až +70 °C
Rozsah skladovacích teplot	-40 °C až +70 °C

Průvodní dokumentace

Návod k obsluze RC20	2312.010.01
Zánamník	6000002011
Technický list	6000002021

Set

Type designation	PN (RN)	Name
RC20	2312.000.01	Remote control unit set