

RM23 - Handset with control

Type designation: **RM23**

PN (RN): **2313.100.40**

The handset with control is intended to control RF23 transceiver. Besides the basic functions of radio channel monitoring, transceiver keying and voice modulation, it features channel selection and step volume change. The device includes a two-row LCD display (2 x 8 characters), which displays channel number, frequency and network name. It also shows other incoming events, such as received FLASH, ALERT and short text messages. The RM23 is equipped with two keys on the side - PTT and tone signaling. The front side features an LCD display and two function keys underneath it. The speaker grid is located above the display. RM23 is linked with the transceiver with a spiral cord that comes out of the bottom section and is terminated with a standard audio-frequency six-pin connector according to MIL-DTL-55116. The connector is connected to the appropriate transceiver AF connector. The RM23 design makes it waterproof to 1 m and resistant to falls.

Technické parametry

Typ komunikačního protokolu	PRC20
Parametry asynchronní komunikační linky	asynchronní, 57600 Bd
Maximální délka propojovacího kabelu	2 m
Modulační napětí do radiostanice	10 mV
Impedance reproduktoru	8 Ω
Kmitočet tónové výzvy	1000 Hz ± 200 Hz
Typ propojovacího konektoru	6 pinů, U229
Hmotnost	0,3 kg
Rozsah pracovních teplot	-30 °C až +70 °C
Rozsah skladovacích teplot	-40 °C až +70 °C