

# NM13 - Mobile charger

Type designation: **NM13**

NSN: **6130160038293**

PN (RN): **7004.100.02**

KČN: **0068600200062**

The charger is used for charging of the single battery pack RF13.1 by a constant current. This charger makes possible the charging of the battery pack at mobile sets by means of an on-board mains of 12 V or 24 V. Temperature increase of the battery pack above +43 °C causes the standard charging current switch-off and consequently the trickle charge mode is switched on. The chargers can be fixed to horizontal or vertical surfaces with four M4 screws. They are connected to the on-board mains by means of a power cable with a cigarette lighter adapter, which is included with the charger. The battery pack is fastened to the charger with a lever closure. The charging stops automatically.

## Technické parametry

<b>Rozsah napájecích napětí</b>	10 V až 33 V
<b>Nabíjecí proud</b>	400 mA
<b>Doba nabíjení</b>	(14 až 16) hodin
<b>Konzervační proud</b>	(30 ± 15) mA
<b>Rozsah pracovních teplot</b>	-20 °C až +50 °C
<b>Rozsah teplot při nabíjení</b>	-20 °C až +40 °C
<b>Rozměry [š x v x h]</b>	192 mm x 68 mm x 81 mm
<b>Hmotnost</b>	max. 1 kg

## Průvodní dokumentace

<b>Návod k obsluze NM13</b>	7004.010.01
<b>Záznamník</b>	6000002011
<b>Technický list</b>	6000002021

## Set

Type designation	PN (RN)	Name
NM13	7004.000.02	Mobile charger

## Batteries

Type designation	PN (RN)	Name
RF13.1	7000.000.02	Rechargeable battery pack set