

RF13.51R - Headset

Type designation: **RF13.51R**

NSN: **5965160038958**

PN (RN): **2023.100.61**

KČN: **0064334000686**

The headset is designed for the situations when the RF13 or RF20, RF1301 operator is in need of free hands for other activities. It can be worn for long periods of time and works with a helmet or a protective mask on the operator. The gradient microphone works even in a very noisy environment.

Technické parametry

Způsob napájení	z NF konektoru radiostanice
Jmenovité napájecí napětí	7,2 V
Mezní napájecí napětí	min. 6,5 V / max. 15 V
Maximální odebíraný proud	30 mA
Mikrofon	gradientní, elektretový s potlačením okolního hluku
Jmenovitá úroveň modulace do radiostanice	100 mV/2 k Ω
Jmenovitá úroveň výstupního signálu z radiostanice	1,3 V/100 Ω
Maximální trvalý příkon sluchátka	0,5 W
Rozsah pracovních teplot	-30 °C až +60 °C
Hmotnost	max. 0,31 kg

Průvodní dokumentace

Návod k obsluze RF13.51/RF13.52	2023.010.61
Záznamník	6000002011
Technický list	6000002021

Set

Type designation	PN (RN)	Name
RF13.51R	2023.000.61	Headset set